

Y Strainer- Flanged- Stainless steel

Fig.7225

Features

Design Standard: API 598 / DIN3202 F1
Flange according to: DIN 2501 PN16/ANSI B16.5
Size Range: 15 mm(1/2")~200mm(8")

Materials

Part	Material	Standard
Body	Carbon Steel	ASTM A216 WCB
	Stainless Steel	ASTM A351 CF8/CF8M/CF3M
Bonnet	Carbon Steel	ASTM A216 WCB
	Stainless Steel	ASTM A351 CF8/CF8M/CF3M
Screen	Stainless Steel	ASTM A182 F304/F316
Gasket	PTFE	
Plug	Stainless Steel	ASTM A182 F304/F316

Technical data

Working Pressure: PN16
Testing Pressure: Body: 24 bar
Temperature: - 25°C~180°C
Medium: Water, Oil, Gas

Schematic



Dimensions

DN	mm	15	20	25	32	40	50	65	80	100	125	150	200
	inch	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4	5	6	8
L		130	140	155	180	200	220	250	280	320	350	380	500
H		75	90	100	115	130	150	190	225	230	280	300	400
D		95	105	115	140	150	165	185	200	220	250	285	340

WARCO reserves the right to change dimensions without notice.