#### **Bimetal Thermometer**

Fig. 2300

## **Specification**

Thread comply with ISO228/1
Testing standards comply with JB/T 8803

### **Technical data**

Norminal size: 40,63,80,00mm

Pocket length: 45,63,80,100,150,200mm

Connection: BSP 1/2"

**Range:**  $-40 \sim +40 ^{\circ}\text{C}, -30 \sim +50 ^{\circ}\text{C}, -20 \sim +60 ^{\circ}\text{C},$  $0 \sim 120 ^{\circ}\text{C}, 0 \sim 600 ^{\circ}\text{C}$ 


Temperature sensor: Bimetal coil

**Accuracy:** 43,63mm:2.5 80,100mm:2.0

Options: Stainless Steel bulb and pocket

#### **Schematic**





# **Material Specifications**

Part Name	Materials	Specification	
Casing	Carbon Steel	Zinc plated steel	
Window	Glass	-	
Bulb	Stainless Steel	Adjustable at end	
Pocket	Brass	-	

### **Dimensions**

DN		ФД	В	ФС	I
mm	inch	Ψυ	D	Ψ	L
43	1-1/2"	43	9	12	45/63/80/100/150/200
63	2-1/2"	63.5	9	12	45/63/80/100/150/200
80	3"	80	10.5	12	45/63/80/100/150/200
100	4"	100	15	12	45/63/80/100/150/200

WARCO reserves the right to change dimensions without notice.