

Double Flange Type Butterfly Valve

Fig. 3226

Specification

Design in accordance with GB/T 12238,EN593,ISO5211
Flanges comply with EN1092-2,ISO 7005,GB/T 9119
Pressure test according to standards GB/T13927


Technical data

Working Pressure:16bar
(Other pressure ratings are optional)
Dimensions: DN50~DN1400
Test Pressure:Shell:24bar
Seal:17.6bar
Working Temperature:-20°C~120°C EPDM Seat
-10°C~80°C NBR Seat

Product Features

- Valve fully sealed in Bi-directional-EN 12266 (Class A) air-tight class;
- Valve plate finishing spherical sealing surface, low torque, long service life;
- Three self-lubricating bushings on the stem to prevent stem deflection;
- May be installed in any direction;
- Can be installed with single flange;
- Maintenance free.

Schematic



Dimensions

DN	mm	50	65	80	100	125	150	200	250	300
	inch	2	2-1/2	3	4	5	6	8	10	12
A		139	146	150	177	177	198	230	266	300
B		80	89	95	114	125	139	170	198	224
L		108	112	114	127	140	140	152	165	178
F		260	260	260	260	260	260	355	355	505
H		28	28	28	28	28	28	38	38	40

WARCO reserves the right to change dimensions without notice.


Double Flange Type Butterfly Valve

Fig. 3226

Material Specifications

Part Name	Materials	Specification
Body	Ductile Iron	EN-JS 1050
Stem	Stainless Steel	BS970 410 S 21
	Stainless Steel	BS970 431 S 29
Seat	EPDM/NBR	
	Viton/PTFE	
Bushing	PTFE	
	Bronze	EN 1982 CC491K
O-Ring	EPDM / NBR	
Disc	Ductile Iron	EN-JS 1050
	Bronze	EN 1982 CC491K
	Stainless Steel	BS970 304 S15
	Stainless Steel	BS970 316 S16
Drive unit	Aluminium Malleable Iron, Cast Iron	
Disc Coating	Epoxy / Nylon / hala	
	Nickel Plating	

Schematic



Dimensions


DN	mm	50	65	80	100	125	150	200	250	300	350
	inch	2	2-1/2	3	4	5	6	8	10	12	14
A		139	146	150	177	177	198	230	266	300	310
B		80	89	95	114	125	139	170	198	224	254
L		108	112	114	127	140	140	152	165	178	190
L1		152	152	152	152	152	152	250	250	227	227
L2		52	52	52	52	52	52	75	75	81	81
L3		75	75	75	75	75	75	86	86	83	83
L4		45	45	45	45	45	45	63	63	81	81
L5		52	52	52	52	52	52	75	75	81	81
ØW		145	145	145	145	145	180	278	278	278	278

WARCO reserves the right to change dimensions without notice.

Double Flange Type Butterfly Valve

Fig. 3226

Product Drawing



Dimensions

DN	mm	400	450	500	600	700	750	800	900	1000	1200	1400
	inch	16	18	20	24	28	30	32	36	40	48	56
A		340	375	430	500	560	610	620	685	735	917	1005
B		282	315	348	410	500	510	550	625	690	800	980
L		216	222	229	267	292	308	318	330	410	470	530
L1		160	160	160	176	215	215	215	215	215	240	240
L2		94	94	94	125	140	140	140	163	163	236	236
L3		104	104	104	131	146	146	146	170	170	180	180
L4		110	110	110	128	157	157	157	170	170	209	209
L5		181	181	181	200	228	228	228	243	243	302	302
L6		104	104	104	131	146	146	146	170	170	250	250
ØW		290	290	290	385	385	385	385	385	385	450	450

WARCO reserves the right to change dimensions without notice.